

5040D 40 HP 4WD Tractor

 JOHN DEERE

*Excellent drive
with ultimate
comfort*



John Deere
PowerTech Engine
40 HP at 2100 RPM



Dual clutch ensures
non-stop independent
operation of PTO



Helical gears are capable
of taking intermittent
heavy loads



Planetary gear gives equal
distribution of load on the
gear set during operation



Adjustable Rear
wheel in 5 steps



John Deere 5040D Tractor TECHNICAL SPECIFICATION

Model	5040D	
Engine		
Engine Manufacturer	John Deere	
Aspirated Engine Type	Naturally	
Number of Cylinders	3	
Bore x Stroke	106.5 x 110 mm	
Displacement	2.9 liters	
Rated Power (Hp)	40	
Rated Engine	2,100 rpm	
Maximum Engine Torque @1200 rpm	156 Nm	
Fuel Tank	60 liters	
Cooling package	Liquid Cooled	
Air filter	Dry type, Dual Element	
Transmission		
Gearbox Type	Collar Shift, Forward 8 / Reverse 4	
Clutch Type	Single	Dual
Power Take Off (PTO)		
PTO Actuation	Mechanical Independent	
PTO Speed (rpm)	540 @ 2,050 Erpm	540E @ 1,600 Erpm
		540 @ 2,050 Erpm
PTO power (Hp)	34.59 @ 2,100 (rpm)	
Steering and Brakes		
Type of steering	Power Steering	
Type of brake	Mechanical Wet Disc Brakes	

DIMENSIONS AND WEIGHT



Hydraulics	
Type	Open center with ADDC (Automatic Depth&Draft Control)
Total flow	36.1 liters/min
Implement Pump flow rate	22.7 liters/min
Steering Pump flow rate	13.4 liters/min
Lifting Capacity @610 mm from Ball End	1,400 kgf
3 Points Hitch Category	CAT II
Electrical	
Battery	12 V, 88 Ah
Starter	12 V 2.5 kW
Wheels and Tires	
Front Tire	8.0 x 18
Rear Tire	13.6 x 28

for more information, please contact our authorized dealer :

Contact information



John Deere Asia (Singapore) Private Limited

438 Alexandra Road #12-01 Alexandra Point,
Singapore 119958

www.deere.com/asia/en eMarketingJDAP@johndeere.com