



Narrow in Width. Wide in Application.



MFWD



FNR Lever



Best In Class
Lift Capacity



Narrow Track Width



Powerful PTO



Metal Face Seals



Specifications

Engine	
Aspiration	Naturally Aspirated
No. of Cylinders	3
Displacement (L)	1.33
Rated Power (hp)	28.5
Rated Engine Speed (rpm)	2800
Fuel Tank Capacity (liter)	32
Cooling Package	Coolant cooled with overflow reservoir
Air Filter	Dry type, Dual element

Transmission	
Gears	8 Forward x 8 Reverse, FNR SyncReverser
Clutch	Single Dry Clutch

Power Take Off (PTO)	
PTO Actuation	Independent, 6 Splines
PTO Speed (r/min)	540 PTO @ 2492 ERPM, 540E PTO @ 1925 ERPM

Dimensions & Weight	
Total Weight (kg)	1200
Turning Radius with Brakes (mm)	2200
Turning Radius without Brakes (mm)	2900

Factory Fitted Options	
Roll Over Protection System (ROPS), Seat and Seat Belt	

Features	
SyncReverser, Fingerguard, FNR NSS, Radiator Screen, Water Separator, Digital Hour Meter, Underhood with downdraft exhaust muffler, Metal Face Seals	

Note: All options / features may not be available for single variant. Cardan Shaft Cover diameter more than 165 mm should not be used with a 995 mm setting. (i.e. with 5 x 12 and 8.3 x 24 tires)

Hydraulic	
Hydraulic Lift at Hitch Ball	910 kg
Hitch Category	CAT I

Steering & Brake	
Type of Steering	Power Steering
Type of Brake	Mechanical Actuated Oil Immersed Disc Brake

Wheels & Tires	
Option 1	Front: 6 x 14, 4 PR; Rear: 9.5 x 24, 8 PR
Option 2	Front: 5 x 12, 6 PR; Rear: 8.3 x 24, 8 PR

Electrical System	
Battery	12 V, 55 Ah
Alternator	12 V, 50 Amp
Starter	12 V, 1.2 kW




John Deere Genuine Parts
| Economical | Reliable | Easily Available |



** Width specifications are with 5 x 12 front tires and 8.3 x 24 rear tires

For more information, please contact our authorized dealer.



www.JohnDeere.com

This literature has been compiled for broad circulation in Southeast Asia. While general information, pictures and descriptions are provided, some illustrations and text may include finance product options and accessories not available in all regions. Please contact your local dealer for details. John Deere reserves the right to change specification and design of products described in this literature without notice. The green and yellow color scheme, the leaping deer logo and the JOHN DEERE word mark are trademarks of Deere & Company.